



e-Podium Ultra

PeopleLink ePodium Ultra delivers seamless interactivity among various digital devices with its ergonomic design which allows you to collaborate with your partners, customers and business associates with technological ease; it provides great productivity benefits due to its modular form factor, achieving easy mobility of the device

Area of applications

Area of application:

Classroom/Training room/Auditorium

Room Capacity: 60 to 80 seater



Specifications

e-Podium Ultra

BODY MATERIAL

Body	: Metallic
Top	: Metallic
Top Sliding Mechanism	: Yes
Provision for Monitor	: Yes (upto 22 inches)
Electronic Monitor Lift	: Yes
Document Camera Tray	: Yes (Sliding Type)
RFID	: Optional

TABLET MONITOR FEATURES

Screen Size	: 21.5" wide LED
Resolution	: 1920 x 1080
PC Connection	: USB Port
Luminosity	: 250 cd/m2
Input	: HDMI
Number of Colours	: 16.7M
Response time	: 5ms
Contrase ratio	: 1000/1
Operating System	: Windows, Linux, Mac.

ELECTRICAL

Input Voltage	: DC 12V
Power : 100 – 250V AC	: 100 – 250V AC.

Digital Signal Processor

Frequency Range	: 30Hz -15000 Hz
Automatic Echo Cancellation	: Yes
Automatic Gain Control	: Yes
Dynamic Noise Reduction	: Yes
Full Duplex	: Yes
Line Input	: 1x Line Input
Line Output	: 1 x Line Output
USB Audio Port	: 1 x USB Port

Multi Channel Digital Signal

Package Includes

Microphone Options	: 1 lapel + 1 Handheld
Frequencies Response	: 50 Hz-18000 Hz
Antennas	: 2 x 3dBi
Output	: Balanced Out x2, Mixed Out x 1
Volume Control	: Yes
Amplifier	: Yes
Line Input	: 1x Balanced, 2 x Unbalanced.
Phantom	: Yes (15 V for Balanced Input)
Power output @8 ohms	: 50 Watts x2
Minimum impedance	: 8 Ohms
Frequency response	: 20Hz-20000Hz
Speakers (1Pair)	: 50 Watts Speaker (1" Titanium Dome Tweeter, 5.25" Polypropylene Woofer, 90-20KHz Frequency response),

Central Controller

Ethernet	: 1x RJ-45
RS-232 Port	: Total 1 dedicated RS-232 Port
Relay Switch Port	: Screen Up/Screen Down (2 Nos)

Gooseneck Microphone Features: (Optional)

Cartridge	: 20mm Condenser
Frequency Response	: 40-20000 Hz.
Polar Pattern	: Cardioids
Connectors	: 3-Pin XLR

Control Pad

Type	: Buttonpad
Interface :	: RS-232
Power	: 12V
Size	: N/A
Type	: Buttonpad with Buttons: VGA, HDMI, PC, Screen up/ Screen Down, Projector Lift up, Projector Lift Down, Mic Mute/Unmute, Volume Mute/Unmute, Volume Up/Down.

Laptop Interface

Laptop Interface	: Inbuilt
Video Port For laptop	: 1x VGA, 2x HDMI
Audio Port For Laptop	: 1x 3.5mm Stereo Female Port
LAN Port	: 1x RJ-45
USB Ports	: 4x USB 2.0 Ports, 1X USB 3.0 Ports, 1xUSB (Laptop Touch & DSP), 1xUSB (CPU Touch & DSP)
Power Socket	: 3 Pin AC 220 Power Socket
RS-232 Port	: 1X 3 Pin RS-232 Ports, 1 x 9 Pin RS-232 Port.
Video Input Ports	: 2 HDMI x Laptop, 1 HDMI x PC, 1 HDMI x Visualiser
Switcher	: Inbuilt 4 HDMI Input, 2 HDMI Output, 1 VGA Output

CPU (Optional)

Processor	: Intel i3 / i5
RAM	: 4 GB
HDD	: 1000 GB
Operating System	: Windows 10
Keyboard/Mouse	: Yes

CONTENTS

Components

Accessories : 1.5 Mtrs HDMI Cable x2, 3.5mm Male to Male x 1, 1.5 mtrs USB 2.0 M to M x4.

Part code : : **PCU-PDP-EP-ULTRA**